Claims

What is claimed is:

5

10

15

1. A trailer lock comprising a rocket bolt, a lock body, and a chain couple:

wherein rocket bolt is the main body of a long bar, and one end of the rocket bolt has a fixed end with a longer dimension, and the other end of the rocked bolt has a locking bolt, and the inner of the fixed end positioning in the intersection of the fixed end and the main body has a mounting segment;

wherein the inner of one end in the lock body has a lock, and the other end has a mounting segment, and the lock can provide the locking bolt of a rocket bolt for an interlock;

wherein both ends of the chain couple fixing with a mounting part; and the mounting part is a ring with an inner mounting hole for providing the interlock of the mounting segment between the rocket bolt and the lock body.

- 2. The tailor lock according to claim 1, the mounting segment between the rocket bolt and the lock body is a segment with an outer screw thread.
- 3. The tailor lock according to claim 1, the side neighboring to the locking bolt in the main body of the rocket bolt has a hollow hole for an elastic pin to pin-in.
- The tailor lock according to claim 1, the mounting segment between the
 rocket bolt and the lock body can individually mount to a cover with an inner screw hole.
 - 5. The tailor lock according to claim 1, the outer rim of the lock body having a ring drain can individually mount to a cover with an inner screw hole.
- 6. The tailor lock according to claim 1, the main body of the chain couple can be a chain.